

#### **Outline of the Presentation**



- Scientific Needs for improved snow and observations
- Mission Objectives
- Observation Requirements
- The Measurement Principle
- Retrieval methods
- Instrument Parameters
- Sensor and Payload
- The Next Step







## The Need for Improved Snow and Ice Observations



#### Global climate system

 Snow and ice are key elements of the climate systems, not properly represented in climate models. In particular snow mass (SWE) is poorly known.

#### Hydrological and surface/atmosphere exchange processes

Snow cover shows high spatial heterogeneity.
 Spatially detailed data are needed for quantifying surface/ atmosphere exchange and the water cycle



#### Glacier mass balance - climate interactions

- Glacier mass balance is a key climate parameter, responding very sensitive to climate change measured on very few glaciers world-wide
- Models with remote sensing input are needed to obtain the global view


#### Snowmelt and glacier runoff - a crucial water resource

- Snow cover and glacier retreat caused by climate change jeopardize the water supply to hundreds of millions of people.
- New models using spatially detailed snow observations are needed to improve water management and support measures to adapt to changes.



# Snow – A Vital Source of Water strongly affected by Climate Change





Accumulated annual snowfall divided by runoff Barnett et al., *Nature*, 2005

Snow and glacier melt dominates the water supply on many land areas.

Better data are needed to quantify the climate impact on water availability and enable early precautions for future shortages.





# Snow mass (SWE) – poorly known from the local to the global scale



SWE observations are very sparse, and in many parts of the world completely missing

SWE computed by GCMs, LAMs and land surface processes models has large error bars





Total volume of snow-water storage (median and range) for North America by 18 different GCMs – intercomparison AMIP-2 (Frei et al., 2003)

Uncertainty in snow process modelling at local scale: Comparison of 23 point models for one snow station (Sleeper River, Vermont) (Etchevers et al., 2005)





# Primary Mission Objective: Snow and Ice in the Water Cycle



- Quantify the amount and variability of fresh water stored in terrestrial snow packs and snow accumulation on glaciers
- Evaluate and reduce the uncertainty of snow water storage in regional and global water budgets
- Validate and improve predictive hydrologic models to reduce uncertainties in water forecasts
- Validate the magnitude and dynamics of snow and ice processes in climate models with observations and assess the validity of feedbacks represented in the models.
- Improve the representation of snow and ice processes in regional and global climate models to reduce uncertainty in predictions.
- Support development of downscaling techniques for snow distribution at climate model grid scales to local-regional scales.





## Secondary Mission Objectives: Snow and Ice Process Studies and Modelling



- Explore the distribution of snow properties in high-latitude regions with focus on the implications for terrestrial carbon cycling and trace gas exchanges
- Evaluate mass balance of a broad sampling of glaciers and ice sheets worldwide to understand current changes and place them into historical context
- Validate and improve lake ice process models with observations of ice properties to reduce model uncertainty and assess effects of lake ice on surface energy exchanges
- Explore the magnitude and distribution of snow on sea ice and thin sea ice to help understand their role for sea ice thermodynamics and mass balance







## **Observation Requirements**

Variable	Spatial Scale	Sampling	Accuracy (rms)	
<b>Primary Parameters</b>	(regional, global)			
Seasonal Snow Cover				
Water equivalent	200, 500 m	3-15 d	3 cm for SWE ≤ 30 cm; 10%	
Snow extent	100, 500 m	3-15 d	5% of area at HRU	
Glaciers				
Snow accumulation	200, 500 m	15 d	10% of maximum	
<b>Secondary Parameters</b>				
Seasonal Snow Cover				
Melting snow area	100, 500 m	3 d	5% of area at HRU	
Snow depth	200, 500 m	3-15 d	10% at hillslope scale	
Glaciers				
Diagenetic facies types; Glacial lakes				
Lake and River Ice				
Ice area; Freeze up and Melt onset				
Sea Ice				
Type and thickness of thin ice				
Snow on sea ice (SWE, snowmelt onset and area)				






## **Backscattering Signal and Physical Parameters**







Snow parameters affecting microwave propagation in snow packs:

Volume, interaction, and surface backscattering components

#### Main parameters:

- snow water equivalent, SWE
- grain size
- soil background
- liquid water (if melting)

### Further parameters:


- snow depth and density (=SWE)
- grain shape
- stratification






### **SWE Sensitivity to Backscatter**







θ= 30°

Snow density  $\rho$  = 250 kg/m<sup>3</sup>


Grain shape: Ellipsoids

(b/a) = 0.25

Grain equivalent radius d =0.25, 0.50, 0.75 mm

IEM for surface


Radiative transfer model Grain characterisation by DDA





# **Snow Accumulation in Percolation Zone of Glaciers Sensitivity Study**





Broken Line – Percolation Full Line – Percolation and winter snow

Based on dual layer RT Model by J.C. Shi & J. Du

#### Winter snow

(Layer 1): Equivalent particle radius r = 0.2 mm
Ellipsoid axis ratio = 0.50
Snow density = 300 kg/m3
Snow depth = 1m

#### Percolation facies

(Layer 2): Equivalent particle radius r = 2 mm, Ellipsoid axis ratio = 0.50, Snow density = 400 kg/m3, Snow depth semi-infinite






## **Study of Atmospheric Propagation Effects**



Atmospheric transmissivity calculated for statistical atmospheric characteristics from ERA40 data, for Northern Finland, winter conditions

#### **Conclusion:**

- Atmospheric corrections based on climatological mean values are suitable for snow retrievals.
- Further option: atmosph. parameters from ECMWF analysis







# Baseline Version for SWE Retrieval Optimized Inversion of Physical Model




The baseline algorithm for SWE retrieval applies the optimized statistical inversion technique. It uses a radiative transfer model with reduced number of free parameters and applies the Nelder-Mead optimization algorithm.

$$F = \sum_{i=1}^{n} \frac{1}{2\sigma_i^2} \left[ \Phi_i \left( x_1, \dots, x_q; c_{1i}, c_{2i}, \dots, c_{ri} \right) - Z_i \right]^2 + \sum_{j=1}^{q} \frac{1}{2\lambda_j^2} \left( x_j - x_j' \right)^2$$

- $\Phi_{\rm I}$  Forward RT model
- Z<sub>i</sub> Backscatter Measurement
- σ Measurement noise
- x<sub>i</sub> State variables (1, ...., q)
- c<sub>i</sub> Configuration parameters
- $\lambda_i$  A priori standard deviation



- SWE
- volume scattering albedo (ω)
- co/cross pol ratio





#### RT Model for Iterative SWE Retrieval



#### RT model with reduced set of free parameters for iteration

$$\sigma_{pq}^{t}(\theta_{i}) = T_{pq}^{2}(\theta_{t}) \left[ \frac{\omega_{pq}}{2} \cos(\theta_{t}) \left\{ 1 - \exp\left(\frac{-2k'_{e}SWE}{\cos\theta_{t}}\right) \right\} + \sigma_{pq}^{G}(\theta_{t}) \exp\left(\frac{-2k'_{e}SWE}{\cos\theta_{t}}\right) \right]$$

k'<sub>e</sub> – density normalized extinction coefficient


Measurement vector of backscatter:

$$\sigma_i^t = \sum_{i=1}^4 \frac{\omega_i}{2} \cos \theta_t (1 - t_i^2) + \sigma_i^G t_i^2$$

Transmission coefficient

$$t_{i;i=1,2,3,4}^2 = \exp\left(-\frac{2(\omega_i + k'_{a,i=1,3})SWE}{\cos\theta_t}\right)$$


k'<sub>a</sub> – density normalized absorption coefficient estimated from snow temperature





## **Processing Line for SWE Retrieval**











## **CoReH<sub>2</sub>O – Instrument Design Parameters**

Parameter	Ku-band SAR	X-band SAR	
Frequency	17.2 GHz	9.6 GHz	
Polarization	VV, VH		
Swath width, Inc angle	≥ 100 km; 30° to 45° range		
Spatial resolution	≤ 50 m x 50 m (≥ 5 looks)		
NESZ	≤ -20dB VV, ≤ -25dB VH	≤ -23dB VV, ≤ -28dB VH	
Radiom. Stability / Bias	≤ 0.5 dB / ≤ 1.0 dB		
Antenna concept	Single or dual reflector with	multiple beam feed array	
Peak transmitter power	1.2 – 1.5 kW	1.8 – 2.0 kW	
Nr. of ScanSAR beams	6	6	





## **Two Proposed Sensor Concepts**



Antenna & Feed Support

Star tracker


PDHT antenna

X-band antenna (3,3 m x 2,1 r

Living Pl

S/C budgets: 1.1-1.3 tons, 3-4 kW
High downlink rate, single/dual GS
High-end X-band downlink architecture
Compatible with VEGA launcher

Results of 2 parallel pre-phase A studies




Breadboard feed array

Antenna Feeds

S-band ant


Solar Array





## **Proposed Technical Solutions**









## **Example for Phase 1 Orbit Coverage**




#### **3-day Repeat Orbit:**

#### **Motivation -**

To cover time scale of forcing by mid-latitude synoptic systems

#### **Objectives**

- Improve data assimilation techniques and downscaling for geophysical models (land surface, hydrology, LAM, GCM, ...)
- Investigations at specific test sites to advance and validate retrieval and process modeling techniques





Living Pl

## Field Experiments for Ku- and X-band Snow Studies



#### HeliSnow Campaign 2007/08

- ESA-ESTEC
- Univ. **Hamburg**
- ENVEO IT


L-, S-, C-, X-, Ku-Band, co- and cross-pol. measurements at 5 Alpine test sites,



### **Cold Land Processes Experiments CLPX-II**

• 2006-07 Colorado 2007-08 Alaska













## Field Experiments for Ku- and X-band Snow Studies



### HeliSnow Campaign 2007/08

- · ESA-ESTEC
- Univ. Hamburg
- ENVEO IT



L-, S-, C-, X-, Ku-Band, co- and cross-pol.
5 Alpine test sites,






### **Field Campaigns**





## **Cold Land Processes** Experiments CLPX-II en 2006-07 Colorado

- 2007-08 Alaska





MLHW - October 2008

### **Conclusion**



- Snow and ice are crucial elements of the water cycle and rapidly changing elements of the global climate system. The 2007 IPCC Report calls for better representation of snow and ice feedbacks in climate models.
- The CoRe-H<sub>2</sub>O mission addresses these needs by providing spatially detailed observations of snow mass and other snow properties, to advance the modelling snow cover processes and surface/atmosphere interactions.
- The mission preparations triggered major research activities in experiment an theory of microwave interaction with snow and ice at Ku- and X-band.
- A promising, economical technical solution for the dual frequency SAR is proposed by industry, fully compatible with the mission requirements.



## The Next Step:

**Earth Explorer User Consultation Meeting:** 

20 - 21 January 2009

**Belém Cultural Centre** 

Lisbon, Portugal

http://www.congrex.nl/09c01/

**ESA consults the Science Community on down selection of Explorer missions for Phase-A studies** 

Come to the meeting and support CoRe-H<sub>2</sub>O!